

GREASEMASTER

Compac

heavy duty compact grease pump

The greasemaster compac is designed as a simple but rugged grease pump that has a 12 or 24VDC electric motor.

The pump will accept up to 2 fixed displacement pumping elements and operates via an internal waterproof timer card or via the GT1x or GT3x electronic control units.

The integral impellor agitates the grease to keep it fluid and to expel air.

A rubber wiper cleans the reservoir and insures grease in the lower pumping chamber does not cavitate. The pump will operate a progressive divider circuit to suit any small to medium machine.



Specification:

Reservoir Capacity	2kg,3kg. Other sizes available
Grease Specification	Lithium NLGI 2
Motor Voltage	12 or 24VDC
Motor Output Power	3.3W starting torque
Current Max	2.5 amps
Speed-12V	18RPM
Speed-24V	18RPM
Output Pressure	Adjustable up to 200bar
Grease output	18 RPM - 3.6cc per min
Temperature Range	-15c +40c
Filling of reservoir	Via grease nipple
Weight	7kg - full
Size 2kg	210mm w x 300mm h x 270mm d
Size 3kg	210mm w x 360mm h x 270mm d

GREASEMASTER
Compac

Trilube
Lubricating Solutions
PH:(02) 9820 5400

Website: www.trilube.com.au
Email: sales@trilube.com.au
Fax: (02) 9820 5411
Unit 1/17 Pembury Rd Minto NSW 2566